

Model of Maximum CBR Distance Travelled by packets in MANETs using Location-Aware Transmission for Ubicomp.

M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY

Abstract – MANET transmission strategies in MANET are considered good for energy containment and management for ubicomp [62]. Hence research in location-awareness and MANETs remain very significant. It is projected that further development will involve technologies like land-based GPS systems, improved location refresh rates and location accuracy, along with developments of better protocols optimised for transmission following distance criteria. To better tune transmission protocols and achieve optimal MANET performance, one desirable knowledge would be the trends of distance coverages by packets in a ubicomp for varying node densities.

A previous study in this direction was made [26], whereby the metric PPD was devised. In this paper, another metric “Max_CBR_Dist”, derived from PPD is defined and its corresponding trends over varying node densities are presented.

This paper adds a second component after the metric PPD [26] to the area of modelling for managing distance packets travel in ubicomp topography of varying node densities. Designers may use these results towards formulation of better transmission protocols for ubicomp. This research is a follow-up of previous work [1-26].

Key terms: Ubicomp- Ubiquitous Computing, MAUC- Mobile and Ubiquitous Computing, MANET- Mobile Adhoc Network, PPD- Packets_Per_Distance, Max_CBR_Dist – Maximum_CBR_Distance, CBR- Constant Bit Rate.

M. Kaleem GALAMALI,
University of Technology Mauritius (student)
Mauritius

Assoc. Prof Nawaz Mohamudally
University of Technology Mauritius,
Mauritius

1. Introduction

Distance coverage is a predominant factor affecting energy consumption in MAUC. This energy expenditure varies proportional to the square of distance a packet travels [15]. In MANET transmission, the sender node along with all MANET route nodes forward packets corresponding to each CBR. One impact in the topography is that total number of packets circulating within the MANET topography. With increasing node density, this total number of packets is expected to increase. The sender node forwards packets

to the closest neighbour but there is no guarantee that all hops will be of equal distance nor that the first hop is the smallest or biggest one for each CBR. The research questions put forward here are: “What are the maximum hop distance experienced by each CBR? What is the trend observable for this maximum hop count and how does it vary with varying node densities?”

The work presented here, is also empirical based and is built over previous work [26]. It follows from the statement that metric PPD remains a wide scope metric from which other sub-component metrics could be formulated. Each such sub-component metric may have specific characteristics that may be utilised for specific decision making in protocols to be used.

The key contributions of this paper is firstly, the development of a derived metric Max_CBR_Dist, derived from PPD for CBR Packet Per Distance analyses. The definition and rationale of metric Max_CBR_Dist is put forward. Secondly, the model of trend is put forward for the metric Max_CBR_Dist with results for varying node densities from 7 until 56 in a topography of 300 x 300 m². The model proposed is the normal distribution model. The rest of this paper is organised as follows: section 2- New Derived Metric – Maximum_CBR_Distance, section 3- Max_CBR_Dist Trend Assessment over Varying Node Numbers, 4- Conclusion and References.

2. New Derived Metric – Maximum_CBR_Distance.

Following definition of PPD [26], Max_CBR_Dist is defined as the maximum distance coverage noted for the whole of a CBR along a MANET topography. It can also be termed as the longest hop distance noted for a CBR.

MANET routes may vary during a CBR transmission. It is envisageable to have the metric at value 0. This may occur for short durations of transmission with snapshot MANET topology whereby all hops are below 0.5 m even though distance between sender and receiver may be high.

The results of this study may serve towards the same purposes as described in previous paper [26].

3. Max_CBR_Dist - Trend Assessment over Varying Node Numbers.

3.0 Major Observations.

For most of the plots from node numbers 7 until 56, the least value of Max_CBR_Dist has revolved around 21.

The plots are very scattered but as depicted in figure 1(a) for node number 7, the plausible “S” shape of the normal distribution is clearly visible. Hence it is put forward that the metric Max_CBR_Dist follows normal distribution with equation of the form:

$$F(x) = b * (1 / (a * \sqrt{2 * \pi})) * \exp(- (x-c) * (x-c) / 2 * a * a)$$

It can also be read as F(x) equals to a factor (b) times the equation of a normal curve.

The x-coordinate of the peak values tend to increase with increasing node number.

3.1 Tabular Summary of Results.

A tabular summary for results of equations of curves (F(x)) is shown below. Column headings are: A→node number, B→Value of parameter a, C→Value of parameter b, D→ value of parameter c (the adjusted mean), E→ reduced chi-square value of plot F(x), F→ Corresponding figure number.

A	B	C	D	E	F
7	0.016 438 9	0.028 232 1	205.829	0.048 409 1	1(b)
8	0.016 390 4	0.028 090 5	205.653	0.048 455 3	2
9	0.016 167 7	0.027 307 5	207.217	0.044 713 3	3
10	0.017 218 3	0.030 411 3	211.3	0.043 087	4
11	0.017 410 9	0.030 880 2	231.38	0.041 007 7	5
12	0.016 566 6	0.028 502 3	27.001	0.047 092	6
13	0.017 592 5	0.031 131 5	219.341	0.036 961 5	7
14	0.018 559 1	0.034 021 5	222.619	0.032 710 1	8
15	0.017 998 7	0.032 434 7	225.176	0.040 314 2	9
16	0.017 5	0.030 582 3	226.394	0.042 106 5	10
17	0.016 414 3	0.028 131 1	227.478	0.032 947 8	11
18	0.016 790 1	0.029 52	229.628	0.039 948 2	12
19	0.016 987 7	0.029 636 3	229.952	0.035 016 4	13
20	0.017 843 8	0.032 116 5	231.287	0.036 523 4	14
21	0.018 964 6	0.035 194 8	232.883	0.034 724	15
22	0.019 101 6	0.035 595	232.058	0.042 322 5	16
23	0.018 029 5	0.032 975 1	231.548	0.044 550 6	17
24	0.018 697 5	0.034 061 7	235.439	0.037 116 3	18
25	0.018 655 3	0.034 181	237.933	0.036 636	19
26	0.019 965 5	0.037 684 7	235.607	0.044 215 2	20
27	0.020 164 1	0.038 655 2	236.63	0.043 365 2	21
28	0.019 439	0.036 789 4	236.554	0.043 260 1	22
29	0.020 382 5	0.039 758 9	238.043	0.042 739 4	23
30	0.019 110 5	0.036 345 1	238.153	0.043 387	24
31	0.018 553 5	0.034 897 6	240.214	0.045 639	25
32	0.018 961 9	0.035 263 2	240.611	0.043 270 1	26
33	0.019 435 3	0.036 551	242.425	0.051 359 5	27
34	0.019 007 6	0.035 869 9	245.071	0.047 210 2	28
35	0.019 376 8	0.036 854 4	243.855	0.052 990 9	29
36	0.018 859 2	0.035 758 4	244.091	0.047 780 1	30
37	0.019 299	0.037 419 5	244.795	0.047 875 2	31
38	0.019 770 7	0.039 453	245.046	0.041 124 8	32
39	0.020 14	0.039 741 1	245.324	0.038 947 7	33

40	0.020 245 9	0.039 970 8	246.846	0.038 108 2	34
41	0.020 833 2	0.041 880 1	245.93	0.041 547	35
42	0.019 763 1	0.039 043 5	245.945	0.045 446	36
43	0.021 308 3	0.043 440 7	247.991	0.039 989 4	37
44	0.019 129 4	0.037 092 8	248.662	0.052 026 1	38
45	0.019 242 3	0.037 322 7	248.86	0.047 408 7	39
46	0.020 648 2	0.041 103 8	248.45	0.046 211 2	40
47	0.020 284 4	0.040 292 9	248.463	0.040 269 1	41
48	0.020 725 5	0.041 485 5	249.838	0.046 532 3	42
49	0.020 261 9	0.039 907 2	250.208	0.048 259 1	43
50	0.020 024 7	0.038 805 2	251.711	0.043 092 4	44
51	0.020 356 7	0.039 840 3	251.43	0.041 831 2	45
52	0.020 559 5	0.041 242 4	252.115	0.036 330 1	46
53	0.021 108 6	0.042 735 6	252.346	0.037 203 5	47
54	0.021 072 1	0.042 558 1	253.197	0.033 080 3	48
55	0.019 685 8	0.038 248 2	252.23	0.034 012 4	49
56	0.020 209 5	0.039 817 5	254.371	0.037 182 2	50

Table 1: summary of results for Max_CBR_Dist equations of curves node numbers 7-56

3.2 Graphical Plots for Results Obtained.

This analysis is performed in gnuplot in Linux. x-axis distance is in meters.

1. Node Number 7




Figure 1(a): cumulative % CBR against max_CBR distance : node_number 7




Figure 1(b): % cbr for Max_CBR_Dist: node_number 7

2. Node Number 8




Figure 2: % cbr for Max_CBR_Dist: node_number 8
 3. Node Number 9




Figure 6: % cbr for Max_CBR_Dist: node_number 12
 7. Node Number 13




Figure 3: % cbr for Max_CBR_Dist: node_number 9
 4. Node Number 10




Figure 7: % cbr for Max_CBR_Dist: node_number 13
 8. Node Number 14




Figure 4: % cbr for Max_CBR_Dist: node_number 10
 5. Node Number 11




Figure 8: % cbr for Max_CBR_Dist: node_number 14
 9. Node Number 15




Figure 5: % cbr for Max_CBR_Dist: node_number 11
 6. Node Number 12




Figure 9: % cbr for Max_CBR_Dist: node_number 15
 10. Node Number 16




Figure 10: % cbr for Max_CBR_Dist: node_number 16
 11. Node Number 17




Figure 11: % cbr for Max_CBR_Dist: node_number 17
 12. Node Number 18




Figure 12: % cbr for Max_CBR_Dist: node_number 18
 13. Node Number 19




Figure 13: % cbr for Max_CBR_Dist: node_number 19
 14. Node Number 20




Figure 14: % cbr for Max_CBR_Dist: node_number 20
 15. Node Number 21




Figure 15: % cbr for Max_CBR_Dist: node_number 21
 16. Node Number 22




Figure 16: % cbr for Max_CBR_Dist: node_number 22
 17. Node Number 23




Figure 17: % cbr for Max_CBR_Dist: node_number 23
 18. Node Number 24




Figure 18: % cbr for Max_CBR_Dist: node_number 24
 19. Node Number 25




Figure 19: % cbr for Max_CBR_Dist: node_number 25
 20. Node Number 26




Figure 20: % cbr for Max_CBR_Dist: node_number 26
 21. Node Number 27




Figure 21: % cbr for Max_CBR_Dist: node_number 27
 22. Node Number 28




Figure 22: % cbr for Max_CBR_Dist: node_number 28
 23. Node Number 29




Figure 23: % cbr for Max_CBR_Dist: node_number 29
 24. Node Number 30




Figure 24: % cbr for Max_CBR_Dist: node_number 30
 25. Node Number 31




Figure 25: % cbr for Max_CBR_Dist: node_number 31
 26. Node Number 32




Figure 26: % cbr for Max_CBR_Dist: node_number 32
 27. Node Number 33




Figure 27: % cbr for Max_CBR_Dist: node_number 33
 28. Node Number 34




Figure 28: % cbr for Max_CBR_Dist: node_number 34
 29. Node Number 35




Figure 29: % cbr for Max_CBR_Dist: node_number 35
 30. Node Number 36




Figure 30: % cbr for Max_CBR_Dist: node_number 36
 31. Node Number 37




Figure 31: % cbr for Max_CBR_Dist: node_number 37
 32. Node Number 38




Figure 32: % cbr for Max_CBR_Dist: node_number 38
 33. Node Number 39




Figure 33: % cbr for Max_CBR_Dist: node_number 39
 34. Node Number 40




Figure 34: % cbr for Max_CBR_Dist: node_number 40
 35. Node Number 41




Figure 38: % cbr for Max_CBR_Dist: node_number 44
 39. Node Number 45




Figure 35: % cbr for Max_CBR_Dist: node_number 41
 36. Node Number 42




Figure 39: % cbr for Max_CBR_Dist: node_number 45
 40. Node Number 46




Figure 36: % cbr for Max_CBR_Dist: node_number 42
 37. Node Number 43




Figure 40: % cbr for Max_CBR_Dist: node_number 46
 41. Node Number 47




Figure 37: % cbr for Max_CBR_Dist: node_number 43
 38. Node Number 44




Figure 41: % cbr for Max_CBR_Dist: node_number 47
 42. Node Number 48




Figure 42: % cbr for Max_CBR_Dist: node_number 48
 43. Node Number 49




Figure 46: % cbr for Max_CBR_Dist: node_number 52
 47. Node Number 53




Figure 43: % cbr for Max_CBR_Dist: node_number 49
 44. Node Number 50




Figure 47: % cbr for Max_CBR_Dist: node_number 53
 48. Node Number 54




Figure 44: % cbr for Max_CBR_Dist: node_number 50
 45. Node Number 51




Figure 48: % cbr for Max_CBR_Dist: node_number 54
 49. Node Number 55




Figure 45: % cbr for Max_CBR_Dist: node_number 51
 46. Node Number 52




Figure 49: % cbr for Max_CBR_Dist: node_number 55
 50. Node Number 56




Figure 50: % cbr for Max_CBR_Dist: node_number 56

4. Conclusion.

This piece of research was aimed at studying a facet of distance coverage, rounded to nearest meter, by packets in ubicomp in situation of MANET transmission over varying Node densities. This work extends from a previous work [26].

More precisely here, a metric Max_CBR_Dist, to assess the trend of maximum hop distance by packets in a ubicomp topography with varying node densities, is developed. The experimental results presented here remain empirical based. The model put forward is the normal distribution model.

The assumptions stated in previous paper [21] hold, e.g availability of lightweight algorithms for location-aware transmission in mobile environments, lightweight MAUC OS supports for efficient binding/unbinding of MANET nodes and appropriate multi-threading/parallel communication in modules of MANET nodes.

The further work identified may include: trend analyses of parameters of equations for the model, formulating methods of predictability for metric Max_CBR_Dist and its trend and reporting observations of certain critical values identified. The purposes of this metric is also open for refinement together with its applicability in MANET transmission protocols. Development of further sub-component metrics for metric PPD remain desirable.

References

[1] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Towards Dependable Pervasive Systems-A Position and Vision Paper, CEET 2014
 [2] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Energy Savings achievable with Location-aware Node-to-Node Transmission in UbiComp, CEET 2014
 [3] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Energy Savings achievable

with Location-aware Node-to-Node Transmission in UbiComp Using Location Refresh Intervals, CEET 2014
 [4] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Energy Savings achievable with Location-aware Transmission in UbiComp Using Relays, CEET 2014
 [5] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Mathematical modeling of need of exact number of relays to ensure seamless mobility in mobile computing, CEET 2014
 [6] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Modelling of need for multiple relays for ensuring seamless mobility, CEET 2014
 [7] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Investigation of prominence of placements of relays in a ubicomp topography,
 [8] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of energy savings achievable with location-aware transmission in ubicomp using optimised number of relays.
 [9] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Investigation of Prominence of Placements of Optimised Number of Relays in a UbiComp Topography using Location-Aware Transmission, CEET 2015.
 [10] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Extending Node Battery Availability in UbiComp with Location-Aware Transmission, CEET 2015.
 [11] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Extending Node Battery Availability in UbiComp with Location-Aware Transmission using Location Refresh Intervals, CEET 2015.
 [12] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Extending Node Battery Availability in UbiComp with Location-Aware Transmission using Uniformly Placed Relays, CEET 2015.
 [13] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Extending Node Battery Availability in UbiComp with Location-Aware Transmission Using Optimally Placed Relays, CEET 2015.
 [14] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Sender Node Energy Savings Achievable with Location-Aware MANET Transmission in UbiComp. ACCN 2016
 [15] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Overall Node Energy Savings Achievable with Location-Aware MANET Transmission in UbiComp. ACCN 2016
 [16] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Sender Node Extra Energy Savings Achievable in MANET Against Direct Node-to-Node Transmission Using Location-Aware Transmission in UbiComp. ACCN 2016
 [17] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Overall Node Extra Energy Savings Achievable in MANET against Direct Node-to-Node Transmission Using Location-Aware Transmission in UbiComp. ACCN 2016
 [18] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Energy Consumption Ratio Achievable in MANET Using Location-Aware Transmission in UbiComp. ACCN 2016
 [19] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Minimum Energy Consumption Ratio Achievable in MANET Using Location-Aware Transmission in UbiComp. ACCN 2016
 [20] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Maximum Energy Consumption Ratio Achievable in MANET Using Location-Aware Transmission in UbiComp. ACCN 2016
 [21] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Overall Energy Consumption Fairness Ratio Achievable in MANET Using Location-Aware Transmission in UbiComp. ACCN 2016
 [22] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Overall Energy Consumption Fairness Proportion Achievable in MANET Using Location-

- Aware Transmission for Ubicomp.
- [23] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Minimum Fairness Proportion Achievable in MANET Using Location-Aware Transmission for Ubicomp.
- [24] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Maximum Fairness Proportion Achievable in MANET Using Location-Aware Transmission for Ubicomp.
- [25] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Sender Fairness Proportion Achievable in MANET Using Location-Aware Transmission for Ubicomp.
- [26] M. Kaleem GALAMALI, Assoc. Prof Nawaz MOHAMUDALLY, Model of Distance Travelled by packets in MANETs using Location-Aware Transmission for Ubicomp.
- [27] Markus Bylund and Zary Segall, Towards seamless mobility with personal servers, 2004.
- [28] Masugi Inoue, Mikio Hasegawa, Nobuo Ryoki and Hiroyuki Morikawa, Context-Based Seamless Network and Application Control, 2004
- [29] Xiang Song, Umakishore Ramachandran, MobiGo: A Middleware for Seamless Mobility, College of Computing Georgia Institute of Technology, Atlanta, GA, USA, August 2007
- [30] Budzisz, Ferrús, R., Brunstrom A., Grinnemo, K, Fracchia, R., Galante, G., and Casadevall, F. Towards transport-layer mobility: Evolution of SCTP multihoming, March 2008
- [31] Paul Dourish & Genevieve Bell, Divining a digital future, 2011.
- [32] Xiang Song, Seamless Mobility In Ubiquitous Computing Environments, PhD Thesis, Georgia Institute of Technology, August 2008
- [33] Kevin O Mahony, Jian Liang, Kieran Delaney, User-Centric Personalization and Autonomous Reconfiguration Across Ubiquitous Computing Environments, NIMBUS Centre Cork Institute of Technology, Cork, Ireland, UBICOMM 2012
- [34] Pablo Vidales, Seamless mobility in 4G systems, *Technical Report, University of Cambridge*, Computer Laboratory, Number 656, November 2005
- [35] João Pedro Sousa and David Garlan, Aura: An Architectural Framework for User Mobility in Ubiquitous Computing Environments, School of Computer Science, Carnegie Mellon University, USA, August 2002
- [36] Dennis Lupiana, Ciaran O'Driscoll, Fredrick Mtenzi, Defining Smart Space in the Context of Ubiquitous Computing, Dublin Institute of Technology, Ireland, Special Issue on ICIT 2009 Conference - Web and Agent Systems, 2009
- [37] N.S.V.Shet1, Prof.K.Chandrasekaran2 and Prof. K.C.Shet3, *WAP Based Seamless Roaming In Urban Environment with Wise Handoff Technique*, International Journal of UbiComp (IJU), Vol.1, No.4, October 2010
- [38] Yipeng Yu Dan He Weidong Hua Shijian Li Yu Qi Yueming Wang Gang Pan, FlyingBuddy2: A Brain-controlled Assistant for the Handicapped, Zhejiang University, *UbiComp'12*, September 5-8, 2012.
- [39] Jing Su, James Scott, Pan Hui, Jon Crowcroft, Eyal de Lara Christophe Diot, Ashvin Goel, Meng How Lim, and Eben Upton, Huggle: Seamless Networking for Mobile Applications, 2007
- [40] Rui Han, Moustafa M. Ghanem, Li Guo, Yike Guo*, Michelle Osmond, Enabling cost-aware and adaptive elasticity of multi-tier cloud applications, Future Generation Computer Systems, 2012
- [41] Byrav Ramamurthy, K. K. Ramakrishnan , Rakesh K. Sinha, Cost and Reliability Considerations in Designing the Next-Generation IP over WDM Backbone Networks, 2012.
- [42] Bhavish Aggarwal, Aditya Akella, Ashok Anand, Athula Balachandran, Pushkar Chitnis, Chitra Muthukrishnan, Ram Ramjee and George Varghese, EndRE: An End-System Redundancy Elimination Service for Enterprises, NSDI 2010, San Jose, CA
- [43] Ashok Anand, Vyas Sekar and Aditya Akella, SmartRE: An Architecture for Coordinated Network-wide Redundancy Elimination, SIGCOMM 2009, Barcelona, Spain
- [44] John Breeden II, "Smart-phone battery life could double – without better batteries", Nov 14, 2012
- [45] Andy Boxall, "When will your phone battery last as long as your kindle", December 5, 2012.
- [46] Imielinski, T. and Navas, J.C. (1999). GPS-based geographic addressing, routing, and resource discovery. *Comms. ACM*, Vol. 42, No. 4, pp. 86-92.
- [47] Hightower, J. and Borriello, G. (2001). Location Systems for Ubiquitous Computing. *IEEE Computer*, Vol. 34, No. 8, August, pp. 57-66.
- [48] Harter, A., Hopper, A., Steggle, P., Ward, A. and Webster, P. (2002). The Anatomy of a Context-Aware Application. *Wireless Networks*, Vol. 8, No. 2-3, Mar-May, pp. 187-197.
- [49] Hightower, J., Brumitt, B. and Borriello, G. (2002). The Location Stack: A Layered Model for Location in Ubiquitous Computing. *Proceedings of the 4th IEEE Workshop on Mobile Computing Systems & Applications (WMCSA 2002)*, Callicoon, NY, USA, June, pp. 22-28.
- [50] Graumann, D., Lara, W., Hightower, J. and Borriello, G. (2003). Real-world implementation of the Location Stack: The Universal Location Framework. *Proceedings of the 5th IEEE Workshop on Mobile Computing Systems & Applications (WMCSA 2003)*, Monterey, CA, USA, October, pp. 122-128.
- [51] Ko, Y., & Vaidya, N. H. (2000). Location-aided routing (LAR) in mobile ad hoc networks. *Wireless Networks*, 6(4), 307-321.
- [52] Liao, W.-H., Tseng, Y.-C., & Sheu, J.-P. (2001). GRID: a fully location-aware routing protocol for mobile ad hoc networks. *Telecommunication Systems*, 18(1), 37-60.
- [53] Kuhn, F., Wattenhofer, R., Zhang, Y., & Zollinger, A. (2003). Geometric ad-hoc routing: of theory and practice. In *Proceedings of the ACM (PODC '03)* (pp. 63-72).
- [54] Jiang, X., & Camp, T. (2002). Review of geocasting protocols for a mobile ad hoc network. In *Proceedings of the Grace Hopper Celebration (GHC)*.
- [55] Ko, Y. & Vaidya, N. H. (1999). Geocasting in mobile ad hoc networks: location-based multicast algorithms. In *Proceedings of the IEEE (WMCSA '99)* (pp. 101).
- [56] Mauve, M., Fuler, H., Widmer, J., & Lang, T. (2003). *Position-based multicast routing for mobile ad-hoc networks* (Technical Report TR-03-004). Department of Computer Science, University of Mannheim.
- [57] Xu, Y., Heidemann, J., & Estrin, D. (2001). Geography-informed energy conservation for adhoc routing. In *Proceedings of the ACM/IEEE (MOBICOM '01)* (pp. 70-84).
- [58] Hu, Y.-C., Perrig, A., & Johnson, D. (2003). Packet leashes: a defense against wormhole attacks in wireless ad hoc networks. In *Proceedings of the INFOCOM '03* (pp. 1976-1986).
- [59] Patwari, N., Hero III, A. O., Perkins, M., Correal, N. S., & O'Dea, R. J. (2003). Relative location estimation in wireless sensor networks. *IEEE Transactions on Signal Processing*, 51(8), 2137-2148.
- [60] Baldauf, M., Dustdar, S., & Rosenberg, F. (2007). A Survey on Context Aware Systems. *International Journal of Ad Hoc and Ubiquitous Computing*, Inderscience Publishers. forthcoming. Pre-print from: <http://www.vitalab.tuwien.ac.at/~florian/papers/ijahuc2007.pdf>
- [61] Hong, D., Chiu, D.K.W., & Shen, V.Y. (2005). Requirements elicitation for the design of context-aware applications in a ubiquitous environment. In *Proceedings of ICEC '05* (pp. 590-596).
- [62] Neeraj Tantubay, Dinesh Ratan Gautam and Mukesh Kumar Dhariwal, A Review of Power Conservation in Wireless Mobile Ad hoc Network (MANET)", International Journal of computer Science Issues, Vol 8, Issue 4, No 1, July 2011.
- [63] Wenrui Zhao, Mostafa Ammar and Ellen Zegura, "A Message Ferrying Approach for Data Delivery in Sparse

Mobile Ad Hoc Networks”, *MobiHoc'04*, May 24–26, 2004,
Roppongi, Japan.

About Author (s):

Associate Professor Nawaz Mohamudally works at University of Technology, Mauritius (UTM) and has undertaken supervision of MPhil/PhD Students for many years.



M. Kaleem Galamali is a part-time student (achieved M Phil Transfer on 28.10.2014, currently PhD student) at UTM under supervision of A.P. Nawaz Mohamudally.