Synthesis and characterization of undoped and sliver doped titanium dioxide thin film by using solgel spin coating method

[Mansoor Hussain, Tanveer Ashraf, Tahir Zaidi, Attaullah Shah, M. Quddamah]

Abstract—In this paper, structural and optical properties of undoped and sliver doped titanium dioxide film have been studied. By using Sol-gel method undoped and sliver doped titanium dioxide (TiO₂) thin film synthesis on FTO glass substrate. Sliver has been doped 3%,7%, concentration in titanium dioxide (TiO₂) .Different properties such as, crystal structure, phase identification, thickness, band gap, transmission and absorption spectrum have been studied using X-ray diffraction (XRD), Raman spectroscopy, UV/Vis spectrophotometry. The results showed that undoped and Ag doped TiO₂ thin film annealed at 450°c had anatase phases and there is no Ag peaks in X-ray diffraction.

Keywords— Titanium dioxide, sliver, sol-gel spin coating, structural properties

I. Introduction

Titanium oxide is a semiconductor material having wide range of implementation in photo catalysis, corrosion protective coating, self-cleaning devices, gas sensor, energy storage and optical [1]. All these applications are based on morphology, crystallographic structure and physical properties of different phase of titanium. TiO₂ can show three forms brookite, rutile and anatase as a bulk material while thin film of TiO₂ can exhibit only rutile, anatase and amorphous. By using chemical deposition techniques brookite film can obtained using annealing temperature. Rutile is most stable phase and anatase and brookite can be transferred into rutile by annealing at high temperature [2-4]. Titanium dioxide has a band gap of 3.2ev, 3.0ev, 1.9ev for anatase, rutile and brookite respectively.

Titanium oxide is non toxic and chemically stable having electrochemical, exceptional physical, photoactive and electronic properties [5-8]. Due to its commercial and technological potential, much work has doing on this material [9, 10]. Titanium oxide involve in many applications such as water purification, lithium batteries, dielectric layer, gas sensing, solar cell, resistive switching etc [11-17]. Different method was adopted to increase their

transition metal in TiO_2 thin film provides different changes in its structural and optical properties which is very beneficial for different applications. Silver is among most studied metal as dopant in TiO_2 [18]. It gives better result and efficiency especially in antibacterial properties [19]. Because of this reason, numerous scientists have

efficiency and applicability. By doping rear earth and

Because of this reason, numerous scientists have researched on the growth of thin films of TiO₂ on the multiple substrates i.e. polycarbonate, glasses and copper by using different techniques such as vapor deposition, thermal oxidation and magnetron sputtering [20-22]. Table 1 is explaining the comparison of Ag doped TiO₂ materials [23-28]. In literature very little work is available on the Ag doped TiO₂ specifically on the FTO template using the spin coating technique. In our study FTO templates were used and undoped, 3% and 7% sliver doped TiO₂ films were synthesized by sol-gel spin coating method. optical and structural properties of undoped and sliver doped TiO₂ were studied in detail.

п. Experimental Method

A. Preparation of solutions

0.12 mole solutions was prepared. Silver nitrate (AgNO₃) and titanium isopropoxide ($C_{12}H_{20}O_4Ti$) precursors were used as initial materials to synthesize the undoped and sliver doped solutions. Specific molar ratios of precursors are measured for all Titanium based solutions. Firstly, 0.4 ml of titanium isopropoxide was hydrolyzed in 10 ml ethanol under the magnetic stirring for 20 min under room temperature to get undoped solution. After that 1 ml acetic acid was added in the solution and again stirred for 30 min at magnetic stirrer. For making the doped solution of Ag in TiO_2 , Sliver nitrate (AgNO₃) was used as additional precursor in simple TiO_2 solution. 3% and 7% weighted used for doping and 6.98mg and 16.29mg sliver nitrate precursor used respectively. Sliver doped solution TiO_2 solution stirrer for 4 hours at magnetic stirrer at room temperature.

Mansoor Hussain

National University of Sciences and Technology , Pakistan

Tanveer Ashraf NILOP, Pakistan

Tahir Zaidi

National University of Sciences and Technology, Pakistan

Attaullah Shah

NILOP, Pakistan

Muhammad Quddamah Khokhar

National University of Sciences and Technology, Pakistan

B. Deposition of TiO₂ based films on substrates

Different methods are available for thin film formation but the most simple and less expensive method which used for deposition of solution of silver doped and undoped on FTO template was sol-gel spin coating method. Before the deposition, substrate cleaning process was done. The FTO template was cleaned by an ultrasonic bath in acetone, poly ethylene glycol, ethanol and deionized water respectively,



for each 15 min. Drying process was done in air to remove any surface contamination. After completing the cleaning process, Solution is spin coated at 3000 rpm for 30sec. After the deposition thin film is dried at 100°C for 10 min. This cycle is repeated for 5 times. Annealing was done at 450°c for 30 min in air for good uniform films. Film thickness about 100 nm in both undoped and sliver doped TiO_2 films measured from Ellipsometry. Complete process explains in figure 1.




Fig.1.flow chart of spin coating method of undoped and sliver doped TiO₂ films.

III. Results and discussion

A. XRD Studies

The crystal structure was examined by using X-Ray Diffraction. Figure 2 shows the patterns of undoped and Sliver Doped TiO₂ using XRD. The TiO₂ thin film that was synthesized by the sol-gel spin coating method showed the sharp and intense diffraction peaks at 25.40(101), 48.15(200), 54.67(211), 61.63(204) match with the JCPDS values (pdf card no: 00-021-1272) which correspond to anatase phase. It is clear from XRD patterns that there are no characteristic peaks related to sliver or its oxides of Ag doped films. By increasing Sliver content intensities of peaks decreases and there is slight shift in peaks due to doping. It is reported that sliver doping improves the

crystallization of Titanium dioxide in some cases, while decrease or remain same in other cases [29] . So, it can be examined that the intensities of film peaks showed very little decreasing tendency with increasing the Ag content. Instead of fact that there is a big variation between ionic radius of ${\rm Ti}^{4+}(74.5~{\rm pm})$ and ${\rm Ag}^+(129{\rm pm})$ the existence of Ag content did not cause major varieties in crystallization. * represents the peaks of FTO Template.




Fig.2. XRD patterns of TiO₂ based films.

B. Raman Spectroscopy

To further clarify the structural study of undoped and Agdoped TiO_2 obtain in XRD, Raman measurement were done at room temperature. Figure 3 displays Raman spectra of undoped and silver doped TiO_2 . Typically, Titanium dioxide anatase phase has four Raman vibrational phonon modes, named as E_g , A_{1g} , B_{1g} modes [30]. Figure 3 clearly shows all four Raman vibrational phonon modes of Anatase phase at 148 , 390, 510 , 632. There is no peak regarding to sliver or its oxides seen in Raman spectra. By increasing Sliver content Raman peaks width increases while intensity decreases which indicating degradation of crystalline quality of titanium dioxide thin film due to large size of Ag^+ ions.




Fig.3. Raman spectra of TiO₂ films.



c. Spectrophotometric studies

The undoped and sliver doped TiO_2 films were analyzed by UV-visspectroscopy. Figure 4 shows optical transmission spectra of the undoped and Sliver doped Titanium dioxide thin films in the visible region. Undoped TiO_2 film is transmission is ~35% and with the addition of Ag in TiO_2 film transmission decreases due to structural defect created in the lattice. Overall low transmission rate is due to large thickness of films.




Fig.4. Transmission spectra of undoped and sliver doped TiO₂ films.

Figure 5 shows the absorbance of undoped and sliver doped TiO_2 films. Absorbance of both undoped and sliver doped TiO_2 films sharp decrease in visible region (>350nm). Doped films have smaller absorbance as compared to undoped film. Ag doping can have influence on absorption of light. Doping of Ag can have significantly influence on the absorption of light. By increasing doping amount, it is clear that in absorption spectra absorption edge shift.




Fig.5. Absorbance spectra of undoped and sliver doped TiO₂ films.

The band gap energy of undoped and sliver doped TiO_2 thin films was calculated by using Tauc's relation for direct band gap material from transmission spectra.

$$(\alpha h v)^2 = A(h v - E_g) \tag{1}$$

The absorption coefficient value was calculated using the relation

$$\alpha = \frac{-lnT}{t} \, \text{nm}^{-1} \tag{2}$$

Here t represents thickness and T represent transmission spectra.

Table 1:

Band gap energy values of undoped and sliver doped ${\rm TiO_2}$ films.

Film	E _g (eV)
undoped	3.35 eV
3% Ag	3.31 eV
7% Ag	3.26 eV

Band gap of undoped TiO_2 is 3.35 eV and sliver doped TiO_2 films band gap energy of 3.33 eV and 3.27 eV for 3% and 7% sliver doping concentration respectively. Table 1 shows band gap of all films. Defective energy levels formed below conduction band are responsible of low band gap in sliver doped TiO_2 and these defective energy levels formed due to structural defects. Since the structural defects are related to Ag concentration so band gap energy decreases slowly with the increasing of Ag concentration in Titanium dioxide thin films.

IV. Conclusion

In this study, undoped and sliver doped TiO₂ thin film prepared by low cost and simple sol-gel spin coating method. Structural properties were studies by XRD, Raman spectroscopy and optical properties studies using spectrophotometry. XRD and Raman shows that both undoped and sliver doped films in anatase phase with good crystalline structure. By increasing sliver content crystal quality decreases. The method used in this study is to provide a low cost, low temperature and simple synthesis of titanium dioxide thin film with good properties TiO₂ thin film has large area of application from resistive switching to photo catalysis and sliver doped TiO₂ also large area of applications.



References

- [1] Diebold, U. The surface science of titanium dioxide. *Surface Science Reports* **48**, 53–229 (2003).
- [2] Kuznetsova, I. N., Blaskov, V., Stambolova, I., Znaidi, L. & Kanaev, A. TiO2 pure phase brookite with preferred orientation, synthesized as a spin-coated film. *Materials Letters* 59, 3820–3823 (2005).
- [3] Di Paola, A., Addamo, M., Bellardita, M., Cazzanelli, E. & Palmisano, L. Preparation of photocatalytic brookite thin films. *Thin Solid Films* 515, 3527–3529, doi: 10.1016/j.tsf.2006.10.114 (2007).
- [4] Moret, M. P., Zallen, R., Vijay, D. P. & Desu, S. B. Brookite-rich titania films made by pulsed laser deposition. *Thin Solid Films* 366, 8–10 (2000).
- [5] L.A. Majewski, R. Schroeder, M. Grell, Low-voltage, high-performance organic field-effect transistors with an ultra-thin TiO2 layer as gate insulator, Adv. Funct. Mater. 15 (2005) 1017–1022
- [6] M. Matsui, M. Akaogi, Molecular dynamics simulation of the structural andphysical properties of the four polymorphs of TiO2, Mol. Simul. 6 (1991)239–244.
- [7] F. Labat, P. Baranek, C. Domain, C. Minot, C. Adamo, Density functional theoryanalysis of the structural and electronic properties of TiO2 rutile and anatasepolytypes: performances of different exchange-correlation functionals, J.Chem. Phys. 126 (2007) 154703.
- [8] H. Wang, J.P. Lewis, Effects of dopant states on photoactivity in carbon-dopedTiO2, J. Phys.: Condens. Matter 17 (2005) L209.
- [9] T. Kamegawa, N. Suzuki, H. Yamashita, Design of macroporous TiO 2 thin filmphotocatalysts with enhanced photofunctional properties, Energy Environ. Sci. 4 (2011) 1411–1416.
- [10] M. Takahashi, M. Inoue, R. Ihara, T. Yoko, T. Nemoto, S. Isoda, L. Malfatti, S.Costacurta, P. Innocenzi, Photo-fabrication of titania hybrid films withtunable hierarchical structures and stimuli-responsive properties, Adv. Mater. 22 (2010) 3303–3306.
- [11] Y. Xie, X. Zhao, Y. Chen, Q. Zhao, Q. Yuan, Preparation and characterization of porous C-modified anatase titania films with visible light catalytic activity, J.Solid State Chem. 180 (2007) 3576–3582
- [12] D. Li, H. Haneda, S. Hishita, N. Ohashi, Visible-light-driven NF-codoped TiO2photocatalysts. 2. Optical characterization, photocatalysis, and potentialapplication to air purification, Chem. Mater. 17 (2005) 2596–2602.
- [13] V. Romeas, P. Pichat, C. Guillard, T. Chopin, C. Lehaut, Testing the efficacy andthe potential effect on indoor air quality of a transparent self-cleaningTiO2-coated glass through the degradation of a fluoranthene layer, Ind. Eng. Chem. Res. 38 (1999) 3878–3885.
- [14] J.S. Chen, Y.L. Tan, C.M. Li, Y.L. Cheah, D. Luan, S. Madhavi, F.Y.C. Boey, L.A.Archer, X.W. Lou, Constructing hierarchical spheres from large ultrathinanatase TiO2 nanosheets with nearly 100% exposed (001) facets for fastreversible lithium storage, J. Am. Chem. Soc. 132 (2010) 6124–6130.
- [15] M. Kumar, A.K. Gupta, D. Kumar, Mg-doped TiO2 thin films deposited by lowcost technique for CO gas monitoring, Ceram. Int. 42 (2016) 405–410.
- [16] S.K. Kim, W.-D. Kim, K.-M. Kim, C.S. Hwang, J. Jeong, High dielectric constantTiO2 thin films on a Ru electrode grown at 250 C by atomic-layer deposition, Appl. Phys. Lett. 85 (2004) 4112–4114.
- [17] N.-G. Park, J. Van de Lagemaat, A. Frank, Comparison of dyesensitizedrutile-and anatase-based TiO2 solar cells, J. Phys. Chem. B 104 (2000)8989–8994.
- [18] M. Behnajady, N. Modirshahla, M. Shokri, B. Rad, Enhancement ofphotocatalytic activity of TiO2 nanoparticles by silver doping:photodeposition versus liquid impregnation methods, Global Nest J. 10(2008) 1–7.
- [19] B. Xi, L.K. Verma, J. Li, C.S. Bhatia, A.J. Danner, H. Yang, H.C. Zeng, TiO2 thinfilms prepared via adsorptive self-assembly for self-cleaning applications, ACS Appl. Mater. Interfaces 4 (2012) 1093–1102.
- [20] M. Kitano, K. Funatsu, M. Matsuoka, M. Ueshima, M. Anpo, Preparation ofnitrogen-substituted TiO2 thin film photocatalysts by the radio frequencymagnetron sputtering deposition method and their photocatalytic reactivityunder visible light irradiation, J. Phys. Chem. B 110 (2006) 25266–25272

- [21] D.H. Lee, Y.S. Cho, W.I. Yi, T.S. Kim, J.K. Lee, H.J. Jung, Metalorganic chemical vapor deposition of TiO2: N anatase thin film on Si substrate, Appl. Phys. Lett.66 (1995) 815–816.
- [22] C.-C. Ting, S.-Y. Chen, D.-M. Liu, Structural evolution and optical properties of TiO2 thin films prepared by thermal oxidation of sputtered Ti films, J. Appl.Phys. 88 (2000) 4628–4633.
- [23] F. Bensouici, T. Souier, A.A. Dakhel, A. Iratni, R. Tala-Ighil, M. Bououdina, Synthesis, characterization and photocatalytic behavior of Ag doped TiO2 thinfilm, Superlattices Microstruct. 85 (2015) 255–265.
- [24] A. Guillén-Santiago, S.A. Mayén, G. Torres-Delgado, R. Castanedo-Pérez, A.Maldonado, M.d.l.L. Olvera, Photocatalytic degradation of methylene blueusing undoped and Ag-doped TiO2 thin films deposited by a sol-gel process:effect of the ageing time of the starting solution and the film thickness, Mater.Sci. Eng.: B 174 (2010) 84–87.
- [25] C. He, Y. Yu, X. Hu, A. Larbot, Influence of silver doping on the photocatalyticactivity of titania films, Appl. Surf. Sci. 200 (2002) 239–247
- [26] J. Kaewkhao, P. Limsuwan, P.P.Y.P. Yupapin, S.J. JanJai, K. Ubonchonlakate, L.Sikong, F. Saito, ISEECPhotocatalytic disinfection of P.aeruginosa bacterial Ag-doped TiO2 film, Procedia Eng. 32 (2012) 656–662.
- [27] B. Xin, L. Jing, Z. Ren, B. Wang, H. Fu, Effects of simultaneously doped anddeposited Ag on the photocatalytic activity and surface states of TiO2, J. Phys. Chem. B 109 (2005) 2805–2809.
- [28] X.F. Lei, X.X. Xue, H. Yang, Preparation and characterization of Agdoped TiO2nanomaterials and their photocatalytic reduction of Cr(VI) under visible light, Appl. Surf. Sci. 321 (2014) 396–403.
- [29] B.A. Akgun, C. Durucan, N.P. Mellott, Effect of silver incorporation oncrystallization and microstructural properties of sol–gel derived titania thinfilms on glass, J. Sol-Gel Sci. Technol. 58 (2011) 277–289.
- [30] Huolin Huang, Yannan Xie, Zifeng Zhang, Feng Zhang, Qiang Xu,Zhengyun Wu, Growth and fabrication of sputtered TiO2 based ultraviolet detectors, Appl. Surf. Sci. 293 (2014) 248e254.



About Author (s):



Mansoor Hussain received the B.Sc degree in Electrical Engineering from COMSATS Institute Of Information And Technology, Islamabad, Pakistan in 2015. Presently I am doing Master degree in Electrical Engineering at College of Electrical and Mechanical Engineering, National University of Sciences and Technology, Islamabad, Pakistan. My current area of research is resistive switching.



Tanveer Ashraf did his PhD from institute of semiconductor and solid state physics, Johannes Kepler University Linz Austria, in 2011. Presently he is working as associate professor in National institute of Laser and Optronics Islamabad.



Tahir Zaidi received his Ph.D. degree from Georgia Institute of Technology, School of Electrical and Computer Engineering, United States in 2010 in Compound Semiconductors. Currently, he is Associate Professor with Department of Electrical Engineering, College of Electrical and Mechanical Engineering, National University of Sciences and Technology, Islamabad, Pakistan.



Attaullah Shah received his PhD from Pakistan institute of Engineering and Applied sciences Islamabad Pakistan, in 2014. Currently he is working as associate professor in National institute of Laser and Optronics Islamabad.



Muhammad Quddamah khokhar received the B.Sc degree in Electrical Engineering from Bahauddin Zakariya University, Multan, Pakistan in 2015. Presently he is working toward the Master degree in Electrical Engineering at College of Electrical and Mechanical Engineering, National University of Sciences and Technology, Islamabad, Pakistan. His current area of research is zinc oxide nanowires

